

SAFETY DATA SHEET
CONTACT-FIX TOLUENE FREE



Page: 1

Compilation date: 01-01-18

Revision No: 7

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: CONTACT-FIX TOLUENE FREE, ATF62

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Use of substance / mixture: PC1: Adhesives, sealants.

Company name: AS-ESSENTIALS LTD
Unit 3 Stutton Lane
Tattingstone
Ipswich
Suffolk
IP9 2NZ
Tel: 01473 327510

Emergency tel: 01473 327510; option 2 (not 24 hrs)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: F: R11; Xi: R36/38; N: R51/53; -: R66; -: R67

Classification under CLP: Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Flam. Liq. 2: H225; Skin Irrit. 2: H315; STOT SE 3: H336

Most important adverse effects: Highly flammable. Irritating to eyes and skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

2.2. Label elements

Label elements under CLP:

Hazard statements: H225: Highly flammable liquid and vapour.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET
CONTACT-FIX TOLUENE FREE

Page: 2

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark

GHS09: Environmental



Precautionary statements: P280: Wear.

P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing.

Rinse skin with.

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312: Call a POISON CENTER or doctor if you feel unwell.

P370+378: In case of fire: Use for extinction.

Label elements under CHIP:

Hazard symbols: Highly flammable.

Irritant.

Dangerous for the environment.



Risk phrases: R11: Highly flammable.

R36/38: Irritating to eyes and skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

S16: Keep away from sources of ignition - No smoking.

S23: Do not breathe vapour.

S38: In case of insufficient ventilation, wear suitable respiratory equipment.

S24/25: Avoid contact with skin and eyes.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT substance.

Section 3: Composition/information on ingredients

[cont...]

SAFETY DATA SHEET
CONTACT-FIX TOLUENE FREE

Page: 3

3.2. Mixtures

Hazardous ingredients:

ETHYL METHYL KETONE - REACH registered number(s): 01-2119457290-43

EINECS	CAS	CHIP Classification	CLP Classification	Percent
201-159-0	78-93-3	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	10-30%

HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS <5% N-HEXANE

-	-	Xn: R65; F: R11; Xi: R38; N: R51/53; -: R67	-	10-30%
---	---	---	---	--------

CYCLOHEXANE

203-806-2	110-82-7	F: R11; Xi: R38; Xn: R65; -: R67; N: R50/53	Flam. Liq. 2: H225; Asp. Tox. 1: H304; Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 1: H410; Aquatic Acute 1: H400	10-30%
-----------	----------	---	---	--------

ETHYL ACETATE - REACH registered number(s): 01-2119475103-46

205-500-4	141-78-6	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	1-10%
-----------	----------	---------------------------------	--	-------

N-HEXANE - REACH registered number(s): 01-2119480412-44-0000

203-777-6	110-54-3	F: R11; Xi: R38; Xn: R48/20; Xn: R62; Xn: R65; -: R67; N: R51/53	Flam. Liq. 2: H225; Repr. 2: H361f; Asp. Tox. 1: H304; STOT RE 2: H373; Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 2: H411	<1%
-----------	----------	--	---	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

[cont...]

SAFETY DATA SHEET
CONTACT-FIX TOLUENE FREE

Page: 4

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

[cont...]

SAFETY DATA SHEET
CONTACT-FIX TOLUENE FREE

Page: 5

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area.
Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Specific end use(s): No data available.

Hazardous ingredients:

ETHYL METHYL KETONE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	600 mg/m ³	899 mg/m ³	-	-

CYCLOHEXANE

UK	350 mg/m ³	1050 mg/m ³	-	-
----	-----------------------	------------------------	---	---

ETHYL ACETATE

UK	200 ppm	400 ppm	-	-
----	---------	---------	---	---

N-HEXANE

UK	72 mg/m ³	-	-	-
----	----------------------	---	---	---

8.1. DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: In case of insufficient ventilation wear suitable respiratory equipment.

Hand protection: Protective gloves. Nitrile gloves. Viton gloves. Gloves (solvent-resistant).

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: No special requirement.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Yellow-brown

[cont...]

SAFETY DATA SHEET
CONTACT-FIX TOLUENE FREE

Page: 6

Odour: Characteristic odour
Evaporation rate: Fast-VOC content 74.9%
Oxidising: Non-oxidising (by EC criteria)
Solubility in water: Insoluble
Viscosity: Viscous
Kinematic viscosity: >40 SEC
Viscosity test method: Flow time in seconds in a 3 mm ISO cup (ISO 2431)
Boiling point/range°C: 60
Flammability limits %: lower: 0.6
upper: 11.5
Flash point°C: -30
Autoflammability°C: 200
Vapour pressure: 92kPa@50degC
Relative density: 0.85

9.2. Other information

Section 10: Stability and reactivity

10.1. Reactivity

Other information: Not applicable.

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

10.3. Possibility of hazardous reactions

Chemical stability: Stable under normal conditions. Stable at room temperature.

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

CYCLOHEXANE

ORL	MUS	LD50	813	mg/kg
-----	-----	------	-----	-------

[cont...]

SAFETY DATA SHEET
CONTACT-FIX TOLUENE FREE

Page: 7

ORL	RAT	LD50	12705	mg/kg
-----	-----	------	-------	-------

ETHYL ACETATE

ORL	MUS	LD50	4100	mg/kg
ORL	RAT	LD50	5620	mg/kg
SCU	RAT	LDLO	5	gm/kg

N-HEXANE

IPR	RAT	LDLO	9100	mg/kg
IVN	MUS	LDLO	831	mg/kg
ORL	RAT	LD50	25	gm/kg

Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Other information: Not applicable.

Section 12: Ecological information

12.1. Toxicity

12.2. Persistence and degradability

Ecotoxicity values: No data available.

Persistence and degradability: Biodegradable in part only.

12.3. Bioaccumulative potential

12.4. Mobility in soil

Bioaccumulative potential: No data available.

Mobility: Volatile.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT substance.

[cont...]

SAFETY DATA SHEET
CONTACT-FIX TOLUENE FREE

Page: 8

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Recovery operations: Not applicable.

Disposal of packaging: Arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1133

14.2. UN proper shipping name

14.3. Transport hazard class(es)

Shipping name: ADHESIVES

Transport class: 3

14.4. Packing group

14.5. Environmental hazards

Packing group: II

Environmentally hazardous: Yes

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Specific regulations: Not applicable.

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

[cont...]

SAFETY DATA SHEET
CONTACT-FIX TOLUENE FREE

Page: 9

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H361f: Suspected of damaging fertility.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

R11: Highly flammable.

R36/38: Irritating to eyes and skin.

R36: Irritating to eyes.

R38: Irritating to skin.

R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R62: Possible risk of impaired fertility.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.