

SAFETY DATA SHEET
CELSI-FIX ORIGINAL AO500 CANISTER ADHESIVE



CELSI-FIX ORIGINAL AO500 ADHESIVE CANISTER

SECTION 1; IDENTIFICATION OF THE SUBSTANCES/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name CELSI-FIX ORIGINAL AO500 ADHESIVE CANISTER
Product No. ADHC

1.2. Relevant identified uses of the substances or mixture and uses advised against

Identified uses Spray adhesive

1.3. Details of the supplier of the data sheet

Company name: AS-ESSENTIALS LTD
 Unit 3 Stutton Lane
 Tattingstone
 Ipswich
 Suffolk
 IP9 2NZ
 Tel: 01473 327510

1.4. Emergency telephone number

+44 (0)1473 327510 option 2 (not 24hrs)

SECTION 2; HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and chemical hazards	Extremely Flam. Aerosol - H222
Human health	Carc.2 – H351 Skin. Irrit. 2 – H315 Eye Irrit. 2 – H319 STOT SE 3 – H336
Environment	Not Classified

Classification (1999/45/EEC) Carc.Cat. 3;R40. F+;R12

The full text for all R-Phrases and Hazard statements are displayed in Section 16.

2.2 Label Elements

Contains DICHLOROMETHANE
Label in Accordance with (EC) No. 1272/2008

SAFETY DATA SHEET
CELSI-FIX ORIGINAL AO500 CANISTER ADHESIVE



Signal word	Danger	
Hazard statements		
	H222	Extremely flammable aerosol.
	H280	Contains gas under pressure, may explode if heated
	H351	Suspected of causing cancer
	H315	Causes skin irritation.
	H319	Causes serious eye irritation.
	H336	May cause drowsiness or dizziness
Precautionary Statements		
	P102	Keep out of reach of children
	P210	Keep away from heat/sparks/open flames/hot surfaces – No Smoking.
	P251	Pressurized container: Do not pierce or burn, even after use.
	P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
	P281	Use personal protective equipment as required.
	P501	Dispose of contents/container in accordance with Local Regulations.
Supplementary precautionary statements		
	P273	Avoid release to the environment.
	P280	Contains gas under pressure, may explode if heated .
	P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
	P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in position comfortable for breathing.
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.Continue Rinsing.
	P308+313	If exposed or concerned: Get medical advice/attention
	P410+412	Protect from sunlight. Do not expose to temperatures Exceeding 50°C/122°F.

Supplement label information

2.3. Other hazards

Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn even after use. Do not spray on naked flame or any incandescent material – NO SMOKING.

SAFETY DATA SHEET
CELSI-FIX ORIGINAL AO500 CANISTER ADHESIVE

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

DICHLOROMETHANE	10-30%
CAS-No.: 75-09-2	EC No.: 200-853-9
Classification (EC 1272/2008) Carc.Cat 2 – H351 Skin Irrit Cat 2 – H315 Eye Irrit Cat 2 – H319 STOT SE Cat 3 – H336	Classification (67/548/EEC) Carc Cat 3:R40

PETROLEUM GASES LIQUIFIED	30-40%
CAS- No.: 68476-85-7	EC No.: 270-704-2
Classification (EC 1272/2008) Flam. Gas 1- H220	Classification (67/548/EEC) F+;R12

The full text for all R-Phrases and hazard statements are displayed in Section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

General information

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

Inhalation

Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.

Ingestion

DO NOT induce vomiting. Get medical attention immediately

Skin contact

Wash the skin immediately with soap and water. Promptly remove clothing if soaked through and wash as above. Get medical attention if any discomfort continues.

Eye Contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

SAFETY DATA SHEET

CELSI-FIX ORIGINAL AO500 CANISTER ADHESIVE

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling section 2.2, and/or in section 11.

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Extinguishing media

Fire can be extinguished using: foam; carbon dioxide; dry powder

5.2 Special hazards arising from the substance or mixture

Unusual fire & Explosion hazards

Canisters may explode in fire.

Toxic gases/vapours/fumes of: Carbon Dioxide (CO₂). Carbon Monoxide (CO)

5.3 Advice for firefighters

Wear self contained breathing apparatus.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Avoid skin and eye contact. Ensure adequate ventilation. Avoid breathing vapours, mist or gas. Wear personal protective equipment (see section 8).

6.2 Environmental precautions

Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environment Agency or other regulatory body. Do not discharge into drains or watercourses or onto the ground.

6.3 Methods and material for containment and cleaning up

Provide ventilation and confine spill. Do not allow runoff to sewer. Absorb in vermiculite, dry sand or earth, and place into containers.

6.4 Reference to other sections

Wear protective clothing as described in section 8 of this safety data sheet. For waste disposal see section 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

SAFETY DATA SHEET

CELSI-FIX ORIGINAL AO500 CANISTER ADHESIVE

7.2. Conditions for safe storage, including any incompatibilities

Must not be exposed to direct sunlight or temperatures above 50°C.

7.3 Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Name	STD	TWA – 8 Hrs		STEL – 15 Min		Notes
DICHLOROMETHANE	WEL	100 ppm(Sk)	350 mg/m3(Sk)	300 ppm (Sk)	1060 mg/m3 (Sk)	
PETROLEUM GASES LIQUIFIED	WEL	1000 ppm (Sk)	1250 mg/m3(Sk)	1250 ppm(Sk)	2180 mg/m3(Sk)	

WEL = Workplace exposure limit.

Ingredient comments

8.2 Exposure controls

Protective equipment



Appropriate engineering controls

Observe any occupational exposure limits for the product or ingredients. As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapour or mist.

Eye/face protection

Chemical splash goggles or face shield. Use equipment for eye protection tested and approved under appropriate government standards such as EN 166(EU).

Hand protection

Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Nitrile rubber.

Other skin and body protection

Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Wear protective clothing.

SAFETY DATA SHEET

CELSI-FIX ORIGINAL AO500 CANISTER ADHESIVE

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Use respirators and components tested and approved under appropriate government standards such as CEN (EU).

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

(a) Appearance	Canister/Aerosol.
(b) Odour	Chlorinated Hydrocarbon
c) Odour Threshold	No data available
(d) pH	No data available
(e) Melting point/freezing point	No data available
(f) Initial boiling point and boiling range	40 (°C)
(g) Flash point	Estimated at -35°C
(h) Evaporation point	No data available
(i) Flammability (solid gas)	No data available
(j) Upper/lower flammability Or explosive limits	No data available
(k) Vapour pressure	No data available
(l) Vapour density	No data available
(m) Relative density	No data available
(n) Water solubility	Slightly soluble in water; soluble in chlorinated hydrocarbons
(o) Partition coefficient n-octanol/water	No data available
(p) Auto-ignition temperature	No data available
(q) Decomposition temperature	No data available
(r) Viscosity	No data available
(s) Explosive properties	No data available
(t) Oxidising properties	No data available.

SAFETY DATA SHEET
CELSI-FIX ORIGINAL AO500 CANISTER ADHESIVE

9.2. Other information

Can pressure 70psi.

9.2 Other information

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

No data available.

10.2 Chemical stability

Avoid heat, sparks, and flames, stable under normal conditions.

10.3 Possibility of hazardous reactions

No data available.

10.4 Conditions to avoid

Avoid heat, flames and other sources or ignition. Avoid contact with: Strong oxidising agents, Strong alkalis and Strong mineral acids.

10.5 Incompatible materials

Materials to avoid

Strong acids, strong oxidising substances and strong alkalis.

10.6 Hazardous decomposition products

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO); Carbon Dioxide (CO₂); Phosgene (COCl₂); Hydrogen Chloride (HCl). Slow hydrolysis with water forms hydrochloric acid.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute Toxicity

LD₅₀ Oral – Rat - >2,000 mg/kg

Inhalation

LD₅₀ Inhalation – Rat – 52,000 mg/m³

Skin contact

Skin – Rabbit

Result: Irritating to skin – 24 hr
(Draize Test)

Eye contact

Eyes – Rabbit

Result: Irritating to eyes – 24 hr
(Draize Test)

Carcinogenicity

SAFETY DATA SHEET

CELSI-FIX ORIGINAL AO500 CANISTER ADHESIVE

Carcinogenicity – Rat – Inhalation

Tumorigenic: Carcinogenic by RTECS criteria. Endocrine: Tumours

Limited evidence of carcinogenicity in animal studies.

Suspected human carcinogens

IARC: 2B – Group 2B: Possible carcinogenic to humans (Methylene Chloride)

Specific Target Organ Toxicity – Single Exposure

May cause respiratory irritation.

May cause drowsiness or dizziness

Aspiration Hazard

No data available.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Not regarded as dangerous to the environment. However, contamination of the aquatic or terrestrial environments should be avoided

12.1 Toxicity

Toxicity to fish LC50 – Pimphales promelas (fathead monnow) – 193.00 mg/l – 96 hr
NOEC – Cyprindon variegatus (sheepshead minnow) – 130 mg/l – 96 hr

Toxicity to daphnia and other

Aquatic invertebrates: EC50 – Daphnia magna (Water f;ea) – 1,682.00 mg/l – 48 hr

12.2 Persistence and degradability

Biodegradability result <26% - Not readily biodegradeable

12.3 Bio accumulative potential

Does not bioaccumulate

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB Assessment

Contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

No data available

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: TRANSPORT INFORMATION

14.1 UN Number

SAFETY DATA SHEET

CELSI-FIX ORIGINAL AO500 CANISTER ADHESIVE

UN No. (ADR/RID/ADN)	3501
UN No. (IMDG)	3501
UN No. (ICAO)	3501

14.2 UN proper shipping name

Liquefied gas flammable N.O.S

14.3 Transport hazard class(es)

ADR/RID/ADN class	2.1
ADR/RID/ADN class	Class 2: Gases
ADR Label No	2.1 & 6.1
IMDG Class	2.1
ICAO Class/division	2.1
ICAO Subsidiary risk	6.1
CEFIC TEC® No	20GSF
Air Class	2.1
UK Road Class	2.1
Transport labels	L.Q.



14.4 Packing group

Not applicable.

14.5 Environmental hazards

Environmentally hazardous substance/marine pollutant.

14.6 Special precautions for user

EMS	F-D, S-U
Tunnel restriction code	(D)

14.7 transport in bulk according to Annex II of MARPOL73/78 and the IBC code.

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

Statutory instruments

The chemicals (Hazard information and packaging for supply) regulations 2009 (S.I 2009 No. 716). Control of substances hazardous to health.

SAFETY DATA SHEET

CELSI-FIX ORIGINAL AO500 CANISTER ADHESIVE

Approved code of practice.

Classification and labelling of substances and preparations dangerous for supply. Safety data sheets for substances and preparations.

Guidance notes

Workplace exposure limits EH40. Introduction to Local exhaust ventilation HS(G)37. CHIP for everyone HSG(108).

EU Legislation

Dangerous substance directive 67/548/EEC. Dangerous preparations directive 1999/45/EC. Regulation (EC) No 1907/2006 of the European parliament and of the council of 18 December 2006 concerning the registration, evaluation, authorisation and restriction of chemicals (REACH), establishing a European Chemicals agency, amending directive 1999/45/EC and repealing council regulation (EEC) No 793/93 and commission regulation (EC) No 1488/94 as well as council directive 76/769/EEC and commission directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) 453/2010. Regulation 1272/2008.

15.2 Chemical safety assessment

No data available

SECTION 16: OTHER INFORMATION

General information

This product should be used as directed. For further information consult the product data sheet or contact technical services.

Information sources

This safety data sheet was compiled using current safety information supplied by distributor raw materials.

Revision comments

This safety data sheet supersedes all previous issues and users are cautioned to ensure that it is current. Destroy all previous data sheets and if in doubt contact AS-Essentials Ltd.

Risk phrases in full

R12	Extremely flammable.
R40	Limited evidence of a carcinogenic effect

Hazard statements in full

H220	Extremely flammable gas
H222	Extremely flammable aerosol.
H351	Suspected of causing cancer
H315	Causes skin irritation.
H310	Causes serious eye irritation.
H336	May cause drowsiness or dizziness

Abbreviations

Carc 2	Carcinogen Category 2
--------	-----------------------

SAFETY DATA SHEET

CELSI-FIX ORIGINAL AO500 CANISTER ADHESIVE

Skin Irrit 2	Skin Irritant Category 2
Eye Irritant 2	Eye Irritant Category 2
STOT SE 3	Specific Target Organ Toxicity Single Exposure Category 3
Carc Cat 3	Carcinogen Category 3
Flam Gas 1	Flammable Gas Category 1

ISSUE: REV4

DISCLAIMER

The Information provided herein, especially recommendations for the usage and the application of this products, is provided in good faith, and no liability on the part of AS-Essentials Ltd is stated or implied. No employee of AS-Essentials Ltd has the authority to waive or alter in any way the content of this document.

Due to different materials used, as well as to varying working conditions, production techniques, and the requirements of the end users, all of which are beyond our control, we strongly recommend that thorough and extensive trials are carried out in order to test the suitability of our products with regard to the required processes and applications. This should also include an ageing test which should be applied to all substrates used.

It is also the responsibility of the purchaser and end user of this product to ensure that all appropriate actions necessary for the protection of the environment, and for the health and safety of their employees are observed.

This datasheet replaces all former versions