

# SAFETY DATA SHEET

## Vinyl Primer VP1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** Vinyl Primer VP1

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Adhesive.

**Uses advised against** No specific uses advised against are identified.

#### 1.3. Details of the supplier of the safety data sheet

**Supplier** AS-ESSENTIALS LTD  
Unit 3 Stutton Lane  
Tattingstone  
Ipswich  
Suffolk  
IP9 2NZ  
01473 327510

#### 1.4. Emergency telephone number

**Emergency telephone** +44 01827 69662 (NOT 24HRS - 8am-5pm mon-fri )

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (EC 1272/2008)

**Physical hazards** Flam. Liq. 2 - H225

**Health hazards** Eye Irrit. 2 - H319 STOT SE 3 - H336

**Environmental hazards** Not Classified

##### **Physicochemical**

The product is highly flammable. Vapours may form explosive mixtures with air. Vapours are heavier than air and may travel along the floor and accumulate in the bottom of containers. Vapours may be ignited by a spark, a hot surface or an ember.

#### 2.2. Label elements

##### **Pictogram**



##### **Signal word**

Danger

##### **Hazard statements**

H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

## Vinyl Primer VP1

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe vapours.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/ container in accordance with national regulations.

**Contains** BUTANONE, ACETONE, ETHYL ACETATE

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

<b>BUTANONE</b>	<b>32.5%</b>
CAS number: 78-93-3	EC number: 201-159-0
	REACH registration number: 01-2119457290-43
<b>Classification</b>	
Flam. Liq. 2 - H225	
Acute Tox. 4 - H302	
Acute Tox. 4 - H312	
Acute Tox. 4 - H332	
Eye Irrit. 2 - H319	
STOT SE 3 - H336	
<b>ACETONE</b>	<b>27.0%</b>
CAS number: 67-64-1	EC number: 200-662-2
	REACH registration number: 01-2119471330-49
<b>Classification</b>	
Flam. Liq. 2 - H225	
Eye Irrit. 2 - H319	
STOT SE 3 - H336	
<b>ETHYL ACETATE</b>	<b>22.5%</b>
CAS number: 141-78-6	EC number: 205-500-4
	REACH registration number: 01-2119475103-46-0017
<b>Classification</b>	
Flam. Liq. 2 - H225	
Eye Irrit. 2 - H319	
STOT SE 3 - H336	

The full text for all hazard statements is displayed in Section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

**General information** Get medical attention if any discomfort continues.

## Vinyl Primer VP1

<b>Inhalation</b>	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Get medical attention.
<b>Skin contact</b>	Remove contaminated clothing immediately and wash skin with soap and water.
<b>Eye contact</b>	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	Vapours may cause headache, fatigue, dizziness and nausea.
<b>Ingestion</b>	May cause discomfort if swallowed. May cause stomach pain or vomiting.
<b>Skin contact</b>	Prolonged skin contact may cause redness and irritation.
<b>Eye contact</b>	May cause temporary eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Use fire-extinguishing media suitable for the surrounding fire. Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards</b>	The product is flammable. Heating may generate flammable vapours. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m <sup>3</sup> . The product is highly flammable.
<b>Hazardous combustion products</b>	Does not decompose when used and stored as recommended.

### 5.3. Advice for firefighters

<b>Protective actions during firefighting</b>	Control run-off water by containing and keeping it out of sewers and watercourses. Avoid breathing fire gases or vapours. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke.
<b>Special protective equipment for firefighters</b>	Wear chemical protective suit.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	Wear protective clothing as described in Section 8 of this safety data sheet.
-----------------------------	---

### 6.2. Environmental precautions

<b>Environmental precautions</b>	Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. Do not discharge into drains or watercourses or onto the ground.
----------------------------------	--

## Vinyl Primer VP1

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers.

### 6.4. Reference to other sections

**Reference to other sections** Wear protective clothing as described in Section 8 of this safety data sheet. For waste disposal, see section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Keep away from heat, sparks and open flame. Static electricity and formation of sparks must be prevented. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Keep away from heat, sparks and open flame. Keep container tightly closed. Keep only in the original container.

**Storage class** Flammable liquid storage.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### BUTANONE

Long-term exposure limit (8-hour TWA): WEL 200 ppm(Sk) 600 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): WEL 300 ppm(Sk) 899 mg/m<sup>3</sup>(Sk)

##### ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m<sup>3</sup>

##### ETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 200 ppm

Short-term exposure limit (15-minute): WEL 400 ppm

WEL = Workplace Exposure Limit

**Ingredient comments** WEL = Workplace Exposure Limits

### BUTANONE (CAS: 78-93-3)

<b>Ingredient comments</b>	WEL = Workplace Exposure Limits
<b>Biological limit values</b>	Short Term Value: 300ppm Long Term Value: 200ppm
<b>DNEL</b>	Consumer - Oral; Long term systemic effects: 31 mg/kg bw/day Consumer - Dermal; Long term systemic effects: 412 mg/kg bw/day Workers - Dermal; Long term systemic effects: 1161 mg/kg bw/day Consumer - Inhalation; Long term systemic effects: 106 mg/m <sup>3</sup> Workers - Inhalation; Long term systemic effects: 600 mg/m <sup>3</sup>

## Vinyl Primer VP1

<b>PNEC</b>	- Fresh water; 55.8 mg/l
	- Sediment (Freshwater); 284.7 mg/kg
	- Intermittent release; 55.8 mg/l
	- Sediment (Marinewater); 284.7
	- Marine water; 55.8 mg/l
	- STP; 709 mg/l
	- Soil; 22.5 mg/kg

### ACETONE (CAS: 67-64-1)

**Ingredient comments** WEL = Workplace Exposure Limits

### ETHYL ACETATE (CAS: 141-78-6)

<b>DNEL</b>	Workers - Inhalation; Short term systemic effects: 1468 mg/m <sup>3</sup>
	Workers - Inhalation; Short term local effects: 1468 mg/m <sup>3</sup>
	Consumer - Inhalation; Short term systemic effects: 734 mg/m <sup>3</sup>
	Consumer - Inhalation; Short term local effects: 374 mg/m <sup>3</sup>
	Workers - Inhalation; Long term local effects: 734 mg/m <sup>3</sup>
	Workers - Dermal; Long term systemic effects: 63 mg/kg bw/day
	Workers - Inhalation; Long term systemic effects: 734 mg/m <sup>3</sup>
	Consumer - Dermal; Long term systemic effects: 37 mg/kg bw/day
	Consumer - Inhalation; Long term systemic effects: 367 mg/m <sup>3</sup>

<b>PNEC</b>	- Fresh water; 0.26 mg/l
	- Marine water; 0.026 mg/l
	- Intermittent release; 1.65 mg/l
	- Sediment (Freshwater); 1.25 mg/kg
	- Sediment (Marinewater); 0.125 mg/kg
	- Soil; 0.24 mg/kg
	- STP; 650 mg/l

## 8.2. Exposure controls

### Protective equipment



### Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

### Eye/face protection

The following protection should be worn: Chemical splash goggles.

### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.

### Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear apron or protective clothing in case of contact.

### Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station. Wash contaminated clothing before reuse. Wash hands thoroughly after handling. When using do not eat, drink or smoke.

## Vinyl Primer VP1

<b>Respiratory protection</b>	In confined or poorly-ventilated spaces, a supplied-air respirator must be worn. Wear a respirator fitted with the following cartridge: Gas filter, type AX.
<b>Environmental exposure controls</b>	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Coloured liquid.
<b>Colour</b>	Various colours.
<b>Odour</b>	Acetone.
<b>Odour threshold</b>	Not available.
<b>pH</b>	pH (concentrated solution): 7-8
<b>Melting point</b>	Not available.
<b>Initial boiling point and range</b>	56°C @ 20
<b>Flash point</b>	-18°C CC (Closed cup).
<b>Evaporation rate</b>	Not determined.
<b>Evaporation factor</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	: 1.8%-13%
<b>Other flammability</b>	Not available.
<b>Vapour pressure</b>	Not available.
<b>Vapour density</b>	Not available.
<b>Relative density</b>	0.86 @ 20°C
<b>Bulk density</b>	Not available.
<b>Solubility(ies)</b>	Insoluble in water.
<b>Partition coefficient</b>	Not available.
<b>Auto-ignition temperature</b>	515°C
<b>Decomposition Temperature</b>	Not available.
<b>Viscosity</b>	Kinematic viscosity > 20.5 mm <sup>2</sup> /s.
<b>Explosive properties</b>	Not available.
<b>Explosive under the influence of a flame</b>	Not considered to be explosive.
<b>Oxidising properties</b>	Not available.
<b>Comments</b>	Information given is applicable to the product as supplied.
<b><u>9.2. Other information</u></b>	
<b>Other information</b>	No information required.

## Vinyl Primer VP1

<b>Refractive index</b>	Not available.
<b>Particle size</b>	Not available.
<b>Molecular weight</b>	Not available.
<b>Volatility</b>	Not available.
<b>Saturation concentration</b>	Not available.
<b>Critical temperature</b>	Not available.
<b>Volatile organic compound</b>	This product contains a maximum VOC content of 700 g/l.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

**Reactivity** There are no known reactivity hazards associated with this product.

#### 10.2. Chemical stability

**Stability** No particular stability concerns. Stable at normal ambient temperatures and when used as recommended.

#### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** Not applicable. Not relevant.

#### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition.

#### 10.5. Incompatible materials

**Materials to avoid** Strong oxidising agents. Strong acids. Strong alkalis.

#### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Oxides of carbon. Oxides of nitrogen.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

**Toxicological effects** No information available.

**Other health effects** There is no evidence that the product can cause cancer.

#### Acute toxicity - oral

**ATE oral (mg/kg)** 6,153.85

#### Acute toxicity - dermal

**ATE dermal (mg/kg)** 6,153.85

#### Acute toxicity - inhalation

**ATE inhalation (vapours mg/l)** 61.54

#### Serious eye damage/irritation

**Serious eye damage/irritation** Irritation of eyes is assumed.

#### Respiratory sensitisation

**Respiratory sensitisation** Not determined.

## Vinyl Primer VP1

### Skin sensitisation

**Skin sensitisation** Not determined.

### Carcinogenicity

**Carcinogenicity** Data lacking.

**Target organ for carcinogenicity** Not relevant.

### Reproductive toxicity

**Reproductive toxicity - fertility** Not available.

**Reproductive toxicity - development** This substance has no evidence of toxicity to reproduction.

### Aspiration hazard

**Aspiration hazard** Not anticipated to present an aspiration hazard, based on chemical structure.

**General information** No specific health hazards known.

**Inhalation** Vapour from this product may be hazardous by inhalation.

**Ingestion** May be harmful if swallowed.

**Skin contact** May be harmful in contact with skin.

**Eye contact** May cause blurred vision and serious eye damage.

### Toxicological information on ingredients.

#### BUTANONE

##### Acute toxicity - oral

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 2,000.0

**Species** Rat

**ATE oral (mg/kg)** 2,000.0

##### Acute toxicity - dermal

**Acute toxicity dermal (LD<sub>50</sub> mg/kg)** 2,000.0

**Species** Rabbit

**ATE dermal (mg/kg)** 2,000.0

##### Acute toxicity - inhalation

**Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l)** 20.0

**Species** Rat

**ATE inhalation (vapours mg/l)** 20.0

## SECTION 12: Ecological Information

### 12.1. Toxicity

**Toxicity** The product is not believed to present a hazard due to its physical nature.



## Vinyl Primer VP1

### Ecological information on ingredients.

#### BUTANONE

**Acute toxicity - fish** LC<sub>50</sub>, EC<sub>50</sub>, IC<sub>50</sub>, : 100 mg/l, Algae

**Acute toxicity - aquatic plants** LC<sub>50</sub>, EC<sub>50</sub>, IC<sub>50</sub>, : 100 mg/l, Fish

### 12.2. Persistence and degradability

### 12.3. Bioaccumulative potential

**Partition coefficient** Not available.

### 12.4. Mobility in soil

**Mobility** The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

### Ecological information on ingredients.

#### BUTANONE

**Mobility** The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

### Ecological information on ingredients.

#### BUTANONE

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

### 12.6. Other adverse effects

**Other adverse effects** None known.

### Ecological information on ingredients.

#### BUTANONE

**Other adverse effects** None known.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**General information** Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

## SECTION 14: Transport information

### 14.1. UN number

**UN No. (ADR/RID)** 1133

**UN No. (IMDG)** 1133

## Vinyl Primer VP1

UN No. (ICAO) 1133

UN No. (ADN) 1133

### 14.2. UN proper shipping name

Proper shipping name (ADR/RID) ADHESIVES

Proper shipping name (IMDG) ADHESIVES

Proper shipping name (ICAO) ADHESIVES

Proper shipping name (ADN) ADHESIVES

### 14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID classification code F1

ADR/RID label 3

IMDG class 3

ICAO class/division 3

ADN class 3

### Transport labels



### 14.4. Packing group

ADR/RID packing group II

IMDG packing group II

ADN packing group II

ICAO packing group II

### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

### 14.6. Special precautions for user

EmS F-E, S-D

ADR transport category 2

Emergency Action Code •3YE

Hazard Identification Number (ADR/RID) 33

Tunnel restriction code (D/E)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## Vinyl Primer VP1

<b>National regulations</b>	Health and Safety at Work etc. Act 1974 (as amended). The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended). The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716). Control of Substances Hazardous to Health Regulations 2002 (as amended).
<b>EU legislation</b>	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Commission Regulation (EU) No 453/2010 of 20 May 2010. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### SECTION 16: Other information

<b>Issued by</b>	Compliance
<b>Revision date</b>	01/06/2017
<b>Revision</b>	20
<b>SDS number</b>	21090
<b>Hazard statements in full</b>	H225 Highly flammable liquid and vapour. H302 Harmful if swallowed. H312 Harmful in contact with skin. H319 Causes serious eye irritation. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness.
<b>Store Between</b>	Store Between 5'c - 25'c

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.